


S.No.	DESCRIPTION	QTY.	MATERIAL
1	BODY	1	ASTM A 216 Gr. WCB/WCC/ASTM A 352 Gr. LCB/LCC ASTM A 351 Gr. CF8/CF8M
2	SIDE COVER	1	ASTM A 216 Gr. WCB/WCC/ASTM A 352 Gr. LCB/LCC ASTM A 351 Gr. CF8/CF8M
3	BALL	1	ASTM A 216 Gr. WCB/WCC/ASTM A 352 Gr. LCB/LCC + ENP
4	SEAT	2	PTFE/CFT/GFT/VITON/NYLON
5	BODY SEAL	1	GRAFOIL/PTFE/VITON
6	BODY STUD	AS	ASTM A 193 Gr.B7/B7M/B8M/A 320 Gr. L7
	BODY STUD NUT	REQD.	ASTM A 194 Gr.2H /2HM/A 194 Gr. 8M/Gr. 4
7	STEM	1	AISI-410 /AISI-4140 /AISI-316/17-4PH
8	GLAND PACKING	-	GRAFOIL/PTFE/VITON
9	GLAND	1	AISI-410 /AISI-4140 /AISI-316
10	STEM SEAL	1	PTFE/VITON/CFT
11	GLAND NUT	1	AISI-410 /AISI-4140 /AISI-316



DETAILS-'A'
ANTISTATIC DEVICE

TEST PRESSURE PSig			
CLASS	HYDROSTATIC	AIR	
300	BODY	SEAT	SEAT
	1100	800	80

DESIGN FEATURES	
DESIGN AND DIMENSIONS	API-6D
ENDS FLANGE DIMENSIONS	A.N.S.I. B 16.5
TESTING	API-6D
FIRE SAFE	API-6FA

ALL BELOW SPECIFICATIONS ARE FOR INFORMATORY PURPOSE ONLY, AND ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

12"	648	303	520.7	31.8	16	450.9	381	50.8
10"	568	252	444.5	28.4	16	387.4	323.9	47.8
8"	502	201	381	25.4	12	330.2	269.7	41.1
6"	403	150	317.5	22.2	12	269.7	215.9	36.6
4"	305	100	254	22.2	8	200.2	157.2	31.8
3"	283	74	209.6	22.2	8	168.1	127	28.4
2"	216	49	165.1	19.1	8	127	92	22.4
SIZE NB	'A'	'ØB'	'ØD'	'ØH'	'N'	'ØP'	'ØR'	'T'

NOTES:-

VALVE SIZE 2" TO 6" - LEVER/WRENCH OPERATED
ABOVE 6" - GEAR OPERATED

DESCRIPTION	
CAST STEEL 2 PIECE (F.B.) BALL VALVE FLOATING HANDLE OPERATED CLASS:-300 SIZE:- 2" TO 12"	
DRN:	<p style="text-align: center;">FORWARD ALLOYS AND CASTINGS L.B.S. MARG, BHANDUP BOMBAY</p>
DATE:	
CHKD:	
DATE:	
APPD:	
DATE:	
DRAWING NO.:	
KOC-B21-F2-1(S)/0	